



How to Instructions Screw Back Bezel Leather Cuff



We look forward to bringing you exclusive innovations
and distinctive products this year and beyond.

www.nunndesign.com

NUNN DESIGN SUPPLIES:


Screw Back Bezel Ornate Large Circle -
Antique Copper (sbbolc-cb)

Cuff Bracelet Leather 1.25 inch width
Brown (cbl1.25br-b)

TOOLS NEEDED:

Flush Cutter Pliers (plfc)

Hole Punch Pliers 1.8mm (plhp18)



TO ASSEMBLE THE BRACELET

STEP 1: (Images 1 & 2)

Punch a hole in your surface; leather, fabric, shoes, belts, hats, metal... You can use a pair of needle nose pliers to make sure the hole is big enough for the Screw Back Bezel.

STEP 2: (Images 3-6)

Insert the screw shank through your surface and screw on the nut.

STEP 3: (Image 7)

I like to apply a dab of glue on the base of the nut and then tighten it down with a pair of needle nose pliers. You can even twist the nut down into the leather so it is recessed.

STEP 4: (Images 8 & 9)

Using a pair of flush cutters, trim away the excess screw shank. The screw shank is very heavy duty, so I recommend placing the flush cutters onto the screw right next to the screw. Turn it upside down so when you cut, the excess screw shank won't go flying.

STEP 5: (Image 10)

Using a file or in my case, an emery board, sand down the edge of the shank to make it nice and smooth.

See what I mean? Way too cool! Now, you can make both the focal point of the bezel uniquely yours, but attach it onto the surface that is uniquely yours too!